

CAMERA:

Camera Outer Diameter	4.90"
Drillpipe Running Tool OD	7.90"
Drillpipe Connection	4½ IF
Pressure Rating	4,351 psi
Frame Rate	5 fps HiRes Color
Inspection Diameter	5.5" - 20"

CONTAINER:

Weight	8,800 lbs
Max Gross Weight	10,000 lbs
Dimensions	4.93' x 6.09' x 8.70'



The **WellViewer®** software allows for full digital pan, tilt, zoom and rotate in recorded data.





REMOTE COMMUNICATION TECHNOLOGY

The Vision iO ReadyCAM®, once connected to internet, can broadcast a continuous Live Feed or allow for Remote Control of the camera functions.

ReadyCAM® Advantages:

- **Shipped with it's own conveyance.** No need for drill pipe or a tugger for conveyance. The ReadyCAM® unit is delivered with a built in boom and sheave system.
- **ReadyCAM® records a full downview and sideview of the borehole from the bottom of the tool string.** No need to pan and tilt to obtain the data, but it can zoom in using software during and after the run.
- **Fiber Optic Umbilical** provides superior resolution.

Running Tool Advantages:

- **ReadyCAM® Running Tool can pump up to 10 bpm out in front of the camera.**
- **ReadyCAM® Running Tool protects the dome lens with a metal cage, and it has a safety spring that allows the camera to retract into the Running Tool if the camera is set down on the lens.**

